



TOPO

ACOUSTIC CEILING
BAFFLES



MATERIAL LOGIQ



TOPO

ACOUSTIC CEILING BAFFLE

Topo gives open ceilings a topography. Individual PET felt blades build into a rolling baffle system, and are available in two standard profiles, the angular Zig and the curved Swell. It's a sculptural system engineered with enough range to match your design intent.

KEY INFO

Material:	1/2" recycled PET felt
Acoustics:	Up to 1.05 NRC rating
Fire Rating:	Class A
Warranty:	1 year
Sustainability:	UL GREENGUARD Gold 60% recycled content HPD Declare label

SPECS

Blade Profile:	Zig, Swell
Blade Length:	24" – 108"
Blade Height:	8", 10", 12"
Blade Spacing:	8" on-center
Module Type:	Full, Edge
Suspension Type:	Independent, framed
Installation Method:	Cable, threaded rod, unistrut, t-grid, direct attach
Finishes:	12 Essential colors 26 Luxe colors 10 wood grain textures


CUSTOM OPTIONS

Every Material Logiq system is designed to be adapted – modified in size, shape, finish, and configuration to fit your project, not the other way around.


Blade Profile: Custom profiles available

DETAILS


Module Components



Baffle Profile: Zig




Baffle Profile: Swell




DIMENSIONS & EDGE TYPE

Blade Length, Height, and Spacing




Edge Type

Wave Edge




Level Edge



SUSPENSION TYPE


Independent

Beneficial for installation flexibility, and on-the-jobsite spacing adjustments




Framed

Beneficial for large ceiling installations




INSTALLATION METHOD


Cable




Unistrut



Threaded Rod



T-Grid




LUXE COLORS

COLORS AND FINISHES



Quarry Stone



Taconite Gray



Gunflint



Morel



Driftless Stone



Sandpiper



Prairie Sand



Toasted Grain



Winter Sunrise



Iron Range



Cardinal



Golfinch



Marigold



Superior Fog



Sea Glass



Belize



Deep Lake



Boundary Waters



Wild Lavender




Cornflower



Mint Mist



Spring Bud



Lichen



Evergreen



Spruce Shadow



Northern Night

Due to color variance in monitor and print settings, please verify PET felt color by requesting a material sample.

ESSENTIAL COLORS

COLORS AND FINISHES




White



Silver



Smoke



Gray



Black



Beige




Tan



Brown



Orange



Red



Lime



Blue



Purple

Due to color variance in monitor and print settings, please verify PET felt color by requesting a material sample.

WOOD GRAIN TEXTURES

COLORS AND FINISHES



Ash



Black Walnut



Charred Ash



Cherry



Maple



Peeled Birch



Red Oak



Rough Oak



Teak




White Oak

Due to color variance in monitor and print settings, please verify PET felt color by requesting a material sample.

PERFORMANCE DATA

GRILLA

ACOUSTIC PERFORMANCE



Product	Mounting	Spacing	250 Hz	500 Hz	1000 Hz	2000 Hz	NRC
11.5" PET Felt Baffle	J-Mount	11" o.c.	0.48	0.73	1.23	1.89	1.05

ADDITIONAL TESTING

Fire Rating:	Class A per ASTM E84
Light Reflectance:	87
Fungi Resistance:	High - Passes ASTM C1338

CERTIFICATIONS

